



ASSESSMENT OF SURFACE WATER QUALITY FOR IRRIGATION PURPOSES IN JEMBER DISTRICT, INDONESIA

Retno Wimbaningrum¹⁾, Endang Arisoesilaningih²⁾, Catur Retnaningdyah²⁾,
Serafinah Indriyani²⁾

¹⁾Dept. of Biology, Faculty of MIPA, University of Jember;

²⁾ Dept. of Biology, Faculty of MIPA, University of Brawijaya
wimbaningrumsubagio@gmail.com

ABSTRACT

Irrigated agriculture is dependent on an adequate water supply of usable quality. The analysis of physico-chemical parameters of surface water in Jember District was done for the criteria of irrigation water quality. Surface water comprises spring water, falls, rivers, and tertiary irrigation channels. For this purpose, three sectors or locations were chosen to take twenty seven water samples in the summer season (September to October, 2013). DO, electrical conductivity (EC_w), pH, and water temperature values were measured directly in the field, while analyses of nitrate (NH_3-N), orthophosphate, total dissolved solids (TDS), and bicarbonate (HCO_3^-) was conducted in a laboratory. The results indicated that EC_w , TDS, pH, water temperature, NH_3-N , and orthophosphate were under the limits set out by the Rules of the Republic of Indonesia Government (PP RI) No. 82, 2001, for water quality standard and FAO for irrigation water quality standard. Thus, the surface water of Jember District was considered to be suitable for irrigation at the sampled location.

Key words: Surface water quality; irrigation; physico-chemical parameter; Jember District.

INTRODUCTION

Water in agricultural activities is an important component that is supplied by a network of irrigation channels. Rivers, lakes, and spring water are sources of irrigation water that are facing pollution problems. Agricultural water sources may be of poor quality because of natural causes, contamination, or both (Ayers and Westcot, 1985). Indonesian rivers are polluted due to the discharge of untreated sewage and industrial effluents. The poor water quality of rivers and spring water has an effect on irrigation water quality. In the last century, surface water resources have been polluted to such levels that they could no longer be used in agricultural irrigation (Simsek and Gunduz, 2007).

The quality of irrigation water directly influences the quality of the soil and the crops grown on this soil. Poor irrigation water quality has a negative effect on crop productivity, crop product quality, and public health of consumers and the farmers who come in direct contact with their irrigation water (Qadir *et al.*, 2007; Listkas *et al.*, 2010; Muthana, 2011). Problems originating from irrigation water quality can be categorized into four groups: (1) salinity hazards, (2) infiltration and permeability problems, (3) specific ion toxicity, and (4) miscellaneous problems (Simsek and Gunduz, 2007).

Agricultural activities in Jember District are supported by irrigation water that is supplied by springs. One of the springs lies in the conservation area of Meru Betiri National Park that is Watu Gembuk. Tancak Spring lies in the wild area that is located far from urban areas and industrial activities. We have the assumption that this spring's water quality is good because of its location in the conservation area and far distance from urban areas. Until now,

we could not find information on the water quality of that spring especially quality for irrigation purposes. According to the above mention, it is of importance to assess the water quality of the surface water in Jember District, particularly for irrigation purposes.

MATERIALS AND METHODS

Study area and sampling sites

This study was performed at three stations: Watu Gembuk Spring, Tancak Falls, and Jompo River. Each station was divided into three sub-stations. Watu Gembuk Spring was divided into Watu Gembuk Spring, Watu Gembuk Stream, and a tertiary irrigation channel in the Block of Aren. Two of the first lie in the conservation area of Sanenrejo Resort of Meru Betiri National Park that water source of the tertiary irrigation channel in the Block of Aren. These sub-stations are located between South latitudes 08°23'33.2" to 08°22'04.7" and East longitudes 113°47'32.8" to 113°47'14.2". Tancak Falls was divided into Tancak Falls, Gunung Pasang River, and a tertiary irrigation channel in Payung village, located between South latitudes 08°03'54.0" to 08°07'12.6" and East longitudes 113°37'6.3" to 113°37'12.8". Jompo River sampling station was divided into a part of Jompo river as the first sub-station that is located near spring water, Jompo River as the second sub-station, and a tertiary irrigation channel in Slawu village as the third sub-station whose water flows from Jompo River. The third group of sub-stations lies between South latitudes 08°08'14.8" to 08°09'28.0" and East longitudes 113°40'52.7" to 113°41'22.6".

Sampling and measuring of water quality parameters

The sampling and measuring of water quality parameters were done at three sampling points in each sub-station during the summer season of September to October, 2012. Electrical conductivity (EC_w), water temperature, and pH were directly measured at each sampling point using a portable EC-meter, pH-meter, and thermometer. Water samples were collected at each sampling point using PVC bottles. The water samples were kept at 4°C in a cool box until their analyses in the laboratory of nitrate, orthophosphate, bicarbonate, and total dissolved solids (TDS). The analyses were done using the Brusin method for nitrate, spectrophotometry method for orthophosphate, titrimetry method for bicarbonate, and gravimetry method for TDS (Clesceri *et al.*, 1998). The physico-chemical data were tabulated and analyzed using one sample t test to compare with data set out by the Rules of the Republic of Indonesia Government (PP RI) No. 82, 2001, for water quality standard especially class 2, class 3, and class 4 for plant watering and FAO for irrigation water quality standard using the program SPSS16.0 for Windows.

RESULTS AND DISCUSSION

The values of temperature, pH, EC_w , NO_3-N , TDS, orthophosphate, and HCO_3^- in the springs, falls, rivers, and irrigation channels of the study area are shown in Table 1. The values represent the mean and the range of nine sampling points at each station. The values of pH, EC_w , NO_3-N , TDS, and HCO_3^- are within the permissible limit for irrigated agriculture according to the Rules of the Republic of Indonesia Government (PP RI) No. 82, 2001, of water quality standard especially class 2, class 3, and class 4 for watering plant and

according to Food and Agriculture Organization (FAO) of irrigation water quality standard (Ayers and Westcot, 1985).

The pH values of the surface water of the study area ranged from 7.2 to 7.9. This value is within the permissible limit for irrigated agriculture according to PP RI No. 82, 2001, (5 to 9) and FAO (6.5 to 8.4). The pH values in Jompo River were lower compared with two other stations (Table 1) That condition due to the anthropogenic acidity originated by source such as generated organic substances. Plants can be affected abnormally if the pH value is not suitable (Ayers and Westcot, 1985).

One of the problems originating from irrigation water quality is salinity hazard. This problem was assessed by measuring EC_w and TDS. The values of these parameters indicate the availability of water to plants. The high value of EC_w and TDS in the irrigation water resulted in increased salinity of the soil. If soil salinity increases, usable plant water in the soil solution decreases dramatically. Plants cannot compete with ions in the soil solution for water because the plants can only transpire pure water. The plants wilt because the roots are unable to absorb the water. High concentration of salt in the soil can result in a "physiological" drought condition.

Table 1. Physico-chemical qualities of surface water in Jember District

Physico-chemical parameters	Watu Gembuk Spring (Sanenrejo Resort, Merubetiri National Park)			Tancak Spring (Suci and Payung Village)			Jompo River (Slawu Village)		
	Range	Mean	Sd	Range	Mean	Sd	Range	Mean	Sd
Temp. (°C)	22.7-28.8	25.2	2.6	18-26.4	22.6	3.3	26.6-31.9	30.3	1.9
pH	7.2-7.9	7.7	0.3	7.2-7.6	7.4	0.2	6.9-7.5	7.3	0.2
EC_w (dS/m)	0.2-0.3	0.2	0.1	0.05-0.06	0.06	0.01	0.10-0.15	0.13	0.02
NO_3-N (mg/l)	0.12-0.47	0.24	0.1	0.08-0.39	0.23	0.1	0.89-1.63	1.14	0.23
Orthop. (mg/l)	0.04-0.08	0.52	0.2	0.02-0.05	0.03	0.09	0.06-0.07	0.07	0.01
HCO_3^- (meq/l)	2.23-2.83	2.4	0.2	0.81-1.21	0.97	0.1	1.42-1.82	1.59	0.16
TDS (mg/l)	80-380	181.44	115	220-380	330	54	320-580	431	88.8

Less water is available to plants, even though the soil may appear wet (Joshi *et al.*, 2009; Shahinasi and Kashuta, 2008). According to PP RI No. 82, 2001, the TDS value is within the permissible limit for irrigated agriculture (<1000 mg/l for class 2 and 3, and <2000 mg/l for class 4). According to FAO, the EC_w value of surface water in Jember District falls under no degree of restriction on use because the value ranged from 0.05 to 0.3 dS/m (Table 1). The TDS value ranged from 80 to 580 mg/l (Table 1), falling under two categories of water quality for irrigation according to FAO. The categories are no degree of restriction on use (<450 mg/l) and slight to moderate degree of restriction on use (450 – 2000 mg/l). The source of dissolved solids in water is natural as minerals in soil and anthropogenic as agrochemicals (Kundu, 2012). The source of dissolved solids in the water of Watu Gembuk Spring, Watu Gembuk Stream, Tancak Falls, and Gunung Pasang River are natural as minerals in soil. The locations of the four sub-stations are far from urban and activities areas, representative of the protected area in Jember District. Anthropogenic agrochemicals are the source of dissolved solids in the water of Jompo River and three irrigation channels because the sub-stations are close to agricultural and urban areas.

HCO₃⁻ contents varied from 0.81 to 2.83 meq/l (Table 1). That value of bicarbonate indicates low cations and anions in the water of the study area. According to FAO, the water quality of the surface water in Jember District falls under slight to moderate degree of restriction on use. Bicarbonate, calcium, and sulphate present in irrigation water cause a white coloration of fruits and leaves, which decreases the quality of agricultural products (Ayers and Westcot, 1985).

The range value of NO₃-N in the water surface of the study area was 0.08-1.63 mg/l. The NO₃-N concentration in the Jompo River station was higher (0.89-1.63 mg/l) compared with two other stations (Watu Gembuk Spring station: 0.12-0.47 and Tancak Falls station: 0.08-0.39) (Table 1). The NO₃-N concentration in the Jompo River station is supplied from point and non-point sources. The location of the Jompo River station is close to agricultural and activities areas that contribute to enriched nitrogen. This nitrogen is considered as input to the crops in the directly available form of NO₃-N. The domestic wastes also contribute to the increased NO₃-N concentration of Jompo River station. According to FAO, the NO₃-N value is within the permissible limit for irrigated agriculture and falls under slight to moderate degree of restriction on use (<5mg/l). The problem originating from nitrate is fast plant vegetative growth, delay of plants' reproductive phase, and the soil in full waters.

Phosphate concentration ranged from 0.02 to 0.08 mg/l (Table 1). According to PP RI No. 82, 2001, the NO₃-N value is within the permissible limit for irrigated agriculture (0.2-5 mg/l). Phosphate in the water samples was present when irrigation is intensive in the rice fields, which results in higher surface runoff and water losses to the streams, rivers, and irrigation channels.

CONCLUSION

The values of EC_w, TDS, pH, water temperature, NO₃-N, HCO₃⁻, and orthophosphate of the surface water in Jember District were within the limits set out by the Rules of the Republic of Indonesia Government (PP RI) No. 82, 2001, for water quality standard and FAO for irrigation water quality standard. Thus, the surface water of Jember District was considered suitable for irrigated agriculture at the sampled location.

REFERENCES

- Ayers, R.S., and D.W. Westcot. 1985. *Water Quality for Agriculture, FAO Irrigation and Drainage*. Paper No.(29), Rev.(1), U.N. Food and Agriculture Organization, Rome.
- Clesceri, L.S., A.E. Greenberg, and A.D. Eaton. 1998. *Standard Methods for the Examination of Water and Waste Water*. 20th Ed., Washington
- Joshi, D.M., A. Kumar, and N. Agrawal. 2009. Assessment of the Irrigation Water Quality of River Ganga In Haridwar District. *Rasayan Journal Chemistry* Vol. 2, No. 2:285-292
- Kundu, S. 2012. Assessment of Surface Water Quality for Drinking and Irrigation Purposes: A Case Study of Ghaggar River System Surface Waters. *Bulletin of Environment, Pharmacology & Life Sciences* Vol. 1, Issue 2:1-1
- Listkas, V.D., V.G. Aschonitis, and V.Z. Antonopulos. 2010. Water Quality in irrigation and Drainage Networks of Thessaloniki Plain in Greece Related to Land Use, Water Management, and Agroecosystem Protection. *Environ. Monit. Assess.* 163:347-359

- Muthanna, M.N. 2011. Quality Assessment of Tigris River by Using Water Quality Index for Irrigation Purpose. *European Journal of Scientific Research* 57:15-28
- Qadir, M., D. Wichelns, L. Raschid-Sally, P.S. Minhas, P. Drechsel, A. Bahri, and P. McCornich. 2007. Agricultural Use of Marginal-Quality Water Opportunities and Challenges. *IWMI Part 4*:225-226
- Shahinasi, E., and V. Kashuta. 2008. *Irrigation water quality and its effects upon soil*. BALWOIS 2008-Ohrid, Republic of Macedonia-27:1-6
- Simsek, C., and O. Gunduz. 2007. IWQ Index: A GIS-Integrated Technique to Assess Irrigation Water Quality. *Journal of Environmental Monitoring and Assessment* 128:277-300.